


Resato hand operated spindle pump



Specifications

Description:

The Resato hand operated spindle pump is a screw type positive displacement pressure generator. It is for use in any application where a liquid is to be compressed within a small volume in order to develop pressure.

Main features:

- ✓ Wetted parts are made from stainless steel.
- ✓ Standard delivered with mounting plate.
- ✓ Self adjusting high pressure Teflon packing.
- ✓ Dual spindle bearing and non rotating piston.
- ✓ Connection: M16x1,5 HP-Female.
- ✓ Non rotating shaft for long packing life.
- ✓ 4 large handles for easy operating.
- ✓ All enclosed design, no protruding spindle.
- ✓ Easily mounted to a work bench and maximum pressure may be obtained with a minimum amount of effort by the operator.

Standard models

Model	Pressure rating	Capacity (cm ³)
SP 3	0- 300 bar	65.0
SP 5	0-500 bar	35.0
SP 10	0-1000 bar	17.0
SP 21	0-2100 bar	12.0
SP 42	0-4200 bar	5.3
SP 70	0-7000 bar	3.0

Dimensions

Length	: 470 mm.
Bars across	: 575 mm.
Connection	: M16x1.5-HP-Female

RESATO INTERNATIONAL BV

1e Energieweg 13
P.O. Box 30

NL-9301 LK
NL-9300 AA

Roden – Holland
Roden - Holland

Phone: +31 (0) 50 501 6877
Fax: +31 (0) 50 501 2402

E-mail: hpsales@resato.com
Internet: www.resato.com

Please note that general data and specifications given in this brochure are subject to change without notice.
Feel free to contact our sales department if you need more definite information.