



Pathfinder Foam Caliper

The Pathfinder was specifically designed for initial pipeline proving in lines with no pigging history and/or potential reductions in bore due to debris build up where an operator plans to initiate a pipeline pigging or ILI campaign.

Key benefits:

- Low risk, cost effective solution.
- Established track record.
- Easy to handle and use - specialised technicians not required infield.
- Fast track data analysis and reporting to support infield operations.
- Allows informed decisions to be made on the appropriate type and configurations of pigs to be deployed to clear or inspect the line.

The Pathfinder is currently available from 4" up to 28" nominal size with ATEX certification available for 6" to 18". With a maximum operating temperature of 70°C and a standard pressure of 200bar, it can be used in a wide range of applications and demanding environments.

Online Electronics Limited
+ 44 (0)1224 714 714
OEL-Sales@ik-worldwide.com

online-electronics.com

Typical applications for Pathfinder include:


- Pipeline proving,
- Measuring pipeline geometry and internal bore,
- Detecting and measuring ovality, dents, restrictions, reductions, debris, deport build-up and other anomalies,
- Debris mapping,
- Assessment for pipeline cleaning as part of an operator's flow assurance management strategy.

Design Features

The Pathfinder pig comprises a polyurethane foam pig with a bore measurement sensing system integrally moulded into the foam matrix built in sensor technology measures and records bore changes at multiple points around the circumference of the tool, allowing accurate measurement of changes to internal diameter .

The electronics, battery, and data logging system are housed in a removable stainless-steel pressure vessel in the centre of the pig. On completion of an inspection run, the data logger is removed from the pig for data download and backloading to the PIL facility.

Sensor readings are sampled and stored on a real time basis. The data files are referenced to an onboard clock. Outputs from the caliper sensors, accelerometers and gyros are correlated to identify circumferential welds and known pipeline features such as bends. Comparison with pipe tallies or construction data books where available and flow measurement recorded during the run allows accurate distance measurement.



The Pathfinder foam caliper tool is simple to use. It is possible for the end user to power up, load, launch, run, receive and recover without the need for a dedicated inspection technician. Downloaded data is simply transferred via an internet connection to the UK facility for analysis and report preparation.

General Data:

Size Range	Pipe diameters from 4" to 28"
Foam Carrier Pig	Medium density polyurethane foam
Bore Passing	Full circumferential bore restrictions up to 50% depending on nominal size
Bend Passing	Minimum bend radius of less than 1D
Operating Pressure	200 bar
Operating Temperature	0°C to 70°C
Run Time	60 hours (single pack) 120 hours (dual pack)

